

PD Series, Remote & Self-Contained, Open Produce Merchandisers



Features

- ▶ Decorator colored sides of your choice from Marc's enormous inventory
- ▶ Night Shades lock in your refrigeration overnight
- ▶ Full length mirror to enhance product visibility
- ▶ Freon valve installed on remote and self contained models
- ▶ Dial thermometer for accurate temperature readings
- ▶ Dry storage bins maximizing total storage capacity
- ▶ Enhanced product lighting from top canopy and under lower level of wire baskets with safety sleeves
- ▶ Two levels of wire baskets in long lasting white epoxy
- ▶ Product dividers for wire baskets and main deck
- ▶ Drain is 1" pipe thread - for easy cleaning (drain connection required in field, remote and self-contained models)
- ▶ Front bumper - made of high density PVC for shopping cart impact
- ▶ Side panels have 1/4" plexiglass for maximum visibility and safety.
- ▶ Insulation is full density, solid core urethane
- ▶ Automatic time clocks are standard for self-contained models
- ▶ Mirror finish stainless steel trim, caps, moulding and main deck

Marc's PD Series Open Produce Merchandisers

MODEL	LENGTH	HEIGHT	DEPTH	Unit Installed	Unit recommended (not included)	Storage Bins	Electrical Data	Product Dividers		Approx. Shipping Weight
								Baskets	Main Deck	
PD-6R	72 1/2 "	78 1/2"	34 1/2 "	x	1 H.P*	4	115/1/60 4.0 amps	12	5	700 lbs.
PD-8R	94 1/2 "	78 1/2"	34 1/2 "	x	2 H.P*	6	115/1/60 6.4 amps	18	7	800 lbs.
PD-10R	116 1/2 "	78 1/2"	34 1/2 "	x	3 H.P*	6	115/1/60 6.7 amps	18	9	1000 lbs.
PD-12R	138 1/2 "	78 1/2"	34 1/2 "	x	3 H.P*	8	115/1/60 8.6 amps	24	11	1140 lbs.
PD-6S/C	72 1/2 "	78 1/2"	34 1/2 " plus 3" removeable wall spacer for compressor air flow	1 H.P	x	2	115/1/60 6.4 amps units & fans	12	5	775 lbs.
							230/208-60-1 10.5 amps units & clock			
PD-8S/C	94 1/2 "	78 1/2"	34 1/2 " plus 3" removeable wall spacer for compressor air flow	1 H.P	x	4	115/1/60 6.4 amps units & fans	18	7	930lbs.
							230/208-60-1 10.5 amps units & clock			

NOTE: Designed for use in locations with air conditioning where temperature and relative humidity do not exceed 75% F and 55% RH.

* This size condenser unit is RECOMMENDED for this model. Consult a competent refrigeration mechanic to determine the appropriate size for your specific application. The appropriate condenser will vary depending on length of run, indoor/outdoor use, etc.

